

View Online at <https://aerobasegroup.com/nsn/5935-00-940-7328>

**Body Style:**

Straight shape, external coupling w/backshell

**Overall Length:**

1.709 inches

**Overall Height:**

1.578 inches

**Overall Width:**

1.578 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.250 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.556 inches and 0.587 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

22-55 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

218.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shell Material Specification:**

Qq-a-591 federal specification single material response

**Included Contact Quantity:**

55 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.055 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-26482 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0