

View Online at <https://aerobasegroup.com/nsn/5935-00-940-7981>

Body Style:

Straight shape, external coupling

Overall Height:

Between 0.682 inches and 0.692 inches

Overall Width:

Between 0.682 inches and 0.692 inches

Environmental Protection:

Corrosion resistant and shock resistant and vibration resistant and moisture resistant

Unthreaded Mounting Hole Diameter:

Between 0.110 inches and 0.117 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.496 inches and 0.504 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.496 inches and 0.504 inches

Distance From Mounting Shoulder To Front Face:

Between 0.605 inches and 0.645 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

4000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Special Features:

Terminal added

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0