# NSN 5935-00-941-2287

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-941-2287
Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Straight shape
Overall Length:
1.375 inches
Overall Width:
0.625 inches
Distance Between Mounting Facility Centers:
0.937 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
14 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
32 and 32 and 32
Thread Size:
0.138 inches and 0.138 inches and 0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:

Plastic single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

## NSN 5935-00-941-2287

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:**

14 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.014 gold grains, troy

**Precious Material:** 

Gold

#### **Thread Series Designator:**

Unc and unc and unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0