

View Online at <https://aerobasegroup.com/nsn/5935-00-941-5480>

Body Style:

Straight shape, flush mount

Overall Length:

1.250 inches

Overall Height:

1.000 inches

Overall Width:

2.000 inches

Environmental Protection:

Moisture resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

0.093 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.781 inches

Distance From Mounting Shoulder To Front Face:

0.094 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

5 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

430.0 single mating end 2nd contact grouping

Contact Maximum Dc Voltage Rating In Volts:

2350.0 single mating end 1st contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic melamine single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Insert Material Specification:

Mil-m-14, type cmg military specification single material response single mating end

Included Contact Quantity:

22 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end 1st contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.024 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.