

View Online at <https://aerobasegroup.com/nsn/5935-00-941-5952>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight edge type w/mounting flange

Overall Length:

4.875 inches

Overall Height:

0.850 inches

Overall Width:

0.500 inches

Distance Between Mounting Facility Centers:

Between 4.564 inches and 4.578 inches

Board Accommodated Length:

4.058 inches single board and 4.072 inches single board

Threaded Device Type:

Mounting hole

Board Accommodated Width:

Between 0.080 inches and 0.104 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

840.0 single mating end single contact grouping

Thread Size:

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

25 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.