## NSN 5935-00-942-3900

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-942-3900 **Body Style:** Straight shape **Overall Length:** Between 1.745 inches and 1.765 inches **Overall Height:** 0.904 inches **Overall Width:** Between 0.604 inches and 0.624 inches **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 1.427 inches and 1.447 inches **Mating End Quantity: Contact Position Arrangement Style:** "2, 15" single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Cable Strain Relief Method:** Potting type **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Insert Material Specification:** Mil-m-14, type sdg military specification single material response single mating end

**Included Contact Quantity:** 

15 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

## NSN 5935-00-942-3900

Electrical Receptacle Connector - Page 2 of 2



## **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.015 gold grains, troy and 0.015 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.