## NSN 5935-00-942-5605

**Thread Class:** 

Right-hand
Body Style:
Straight shape
Overall Length:
1.500 inches
Overall Height:
0.530 inches
Overall Width:
0.340 inches

**Thread Direction:** 

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-942-5605

_	Environmental Protection:
١	/ibration resistant
0	Distance Between Mounting Facility Centers:
1	.250 inches
1	Threaded Device Type:
Ν	Mounting stud
Ν	Mating End Quantity:
1	
C	Contact Position Arrangement Style:
7	single mating end
C	Contact Removability:
١	Nonremovable single mating end single contact grouping
C	Contact Maximum Current Rating In Amps:
7	7.5 single mating end single contact grouping
F	Polarization Method:
C	Guide pin/socket
T	Thread Size:
C	0.086 inches
T	Ferminal Location:
E	Back single mating end single contact grouping
C	Contact Material:
C	Copper alloy single mating end single contact grouping
C	Contact Surface Treatment:
C	Gold single mating end single contact grouping
l	nsert Material:
F	Plastic diallyl phthalate single mating end
T	Ferminal Type:
S	Solder well single mating end single contact grouping
l	nsert Material Specification:
	Mil-m-14, type sdg-f military specification single material response single mating end

## NSN 5935-00-942-5605

Electrical Receptacle Connector - Page 2 of 2



## **Unable To Decode:** Unable to decode and unable to decode **Included Contact Quantity:** 26 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.026 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):