## NSN 5935-00-942-6519

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-942-6519 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, flush mount **Overall Length:** 1.109 inches **Overall Height:** Between 3.927 inches and 3.947 inches **Overall Width:** Between 3.365 inches and 3.385 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.995 inches and 1.005 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.870 inches and 2.880 inches **Distance From Mounting Shoulder To Front Face:** Between 0.052 inches and 0.072 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 14 single mating end **Contact Removability:** Removable all mating ends all contact groupings **Polarization Method:** Contact Shell Type: Solid **Connector Locking Method:** Thready Qty Per Inch (tpi): 12 **Thread Size:** 0.312 inches **Terminal Location:** Back all mating ends all contact groupings **Contact Material:** 

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:** 

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

## NSN 5935-00-942-6519

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic melamine all mating ends or plastic phenolic all mating ends
Terminal Type:
Solder well all mating ends all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Type:
Coaxial pin all mating ends all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.028 gold grains, troy and 0.028 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0