## NSN 5935-00-942-9933

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-942-9933 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.850 inches **Overall Diameter:** 1.155 inches **Environmental Protection:** Corrosion resistant and cold resistant and heat resistant and humidity resistant and pressure proof and shock resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** 0.455 inches **Mounting Facility Thickness:** 0.156 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 14-09 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet latch Thready Qty Per Inch (tpi):

20

Thread Size:

0.875 inches

## NSN 5935-00-942-9933

A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Iron alloy 52 single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Glass single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
9 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/double flat
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.009 gold grains, troy and 0.009 silver grains, troy
Precious Material:
Gold and silver
Relationship To Similar Equipment (non-core):
Same as amphenol p/n 67-04h14-9p except w/o face seal
Supplementary Features:
Same as amphenol p/n 67-04h14-9p except w/o face seal
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: