Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-942-9971

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.980 inches
Overall Height:
1.032 inches
Overall Width:
1.032 inches
Environmental Protection:
Vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.713 inches and 0.723 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.713 inches and 0.723 inches
Distance From Mounting Shoulder To Front Face:
0.653 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
10sl-4 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid



# Connector Locking Method:

Externally threaded shell

## Thread Length:

0.438 inches

Thready Qty Per Inch (tpi):

24

### Thread Size:

0.625 inches

**Terminal Location:** 

Back single mating end single contact grouping

### **Contact Material:**

Steel single mating end single contact grouping

### **Contact Surface Treatment:**

Tin single mating end single contact grouping and cadmium single mating end single contact grouping and copper single mating end single

## contact grouping

**Insert Material:** 

Glass single mating end

#### **Terminal Type:**

Solder well single mating end single contact grouping

#### Shell Material:

Steel

### Shell Surface Treatment:

Cadmium and chromate

#### **Included Contact Quantity:**

2 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping

### **Special Features:**

Hermetically sealed

### **Thread Series Designator:**

Unef

### Shelf Life:

N/a

## Unit Of Measure:

--

### Demilitarization:

No

## Fiig:

A039b0