

View Online at <https://aerobasegroup.com/nsn/5935-00-944-3721>

Body Material:

Plastic

Body Style:

Top mount w/molded saddle

Fabrication Method:

Molded

Overall Length:

2.218 inches

Temperature Rating:

-65.0 degrees celsius and 120.0 degrees celsius

Overall Height:

0.585 inches

Overall Width:

0.631 inches

Mounting Hole Diameter:

Between 0.213 inches and 0.223 inches

Body Mounting Hole Accommodation Length:

Between 1.221 inches and 1.241 inches

Body Mounting Hole Accommodation Width:

Between 0.552 inches and 0.572 inches

Mounting Hole Style:

Rectangular, w/rounded ends and two mounting holes/slots

Specific Equipment Accommodated:

Socket relay

Contact Maximum Current Rating In Amps:

5.0

Contact Material:

Copper alloy

Contact Surface Treatment:

Gold

Accommodated Contact Quantity:

8

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 1.834 inches and 1.854 inches

Polarization Type:

Off center hole

Projection Length Above Mounting Surface:

Between 0.178 inches and 0.198 inches

Mounting Method:

Saddle

Mounting Type For Which Designed:

Chassis

Contact Position Arrangement Style:

Triple in line

Contact Maximum Voltage In Volts And Current Type:

2500.0 ac and 2500.0 dc

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.008 gold grains, troy

Precious Material:

Gold

Test Data Document:

96906-ms25322 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

8 solder well

Specification Data:

96906-ms25322 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300