Receptacle Dummy Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-945-1154

2a Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Connector Locking Method: Externally threaded shell Thread Size:
Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Connector Locking Method: Externally threaded shell
Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Connector Locking Method: Externally threaded shell
1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Connector Locking Method: Externally threaded shell
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Connector Locking Method: Externally threaded shell
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Connector Locking Method: Externally threaded shell
Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Connector Locking Method: Externally threaded shell
7.5 single mating end single contact groupingConnector Locking Method:Externally threaded shell
Connector Locking Method: Externally threaded shell
Externally threaded shell
Thread Size:
0.875 inches
Insert Material:
Plastic single mating end
Shell Material:
Aluminum alloy
Special Features:
Arc resistant
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0