Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-945-6384

## **Body Style:** Straight shape **Overall Height:** Between 1.115 inches and 1.135 inches **Overall Width:** Between 2.302 inches and 2.322 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.745 inches and 0.755 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.056 inches and 2.068 inches **Distance From Mounting Shoulder To Front Face:** Between 0.745 inches and 0.755 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 26 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:**

26 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping



Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.026 gold grains, troy Precious Material: Gold Supplementary Features: Mounting method - float

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0