NSN 5935-00-945-7265

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-945-7265 | |
|---|--|
| Thread Direction: | |
| Right-hand | |
| Body Style: | |
| Straight shape | |
| Overall Length: | |
| 1.250 inches | |
| Overall Height: | |
| 0.530 inches | |
| Overall Width: | |
| 0.270 inches | |
| Environmental Protection: | |
| Vibration resistant | |
| Distance Between Mounting Facility Centers: | |
| 1.000 inches | |
| Threaded Device Type: | |
| Mounting stud | |
| Mating End Quantity: | |
| 1 | |
| Contact Removability: | |
| Nonremovable single mating end single contact grouping | |
| Contact Maximum Current Rating In Amps: | |
| 3.0 single mating end single contact grouping | |
| Polarization Method: | |
| Guide pin/socket | |
| Thread Length: | |
| 0.150 inches | |
| Thready Qty Per Inch (tpi): | |
| 56 | |
| Thread Size: | |
| 0.086 inches | |
| Terminal Location: | |
| Back single mating end single contact grouping | |
| Contact Material: | |
| Copper alloy single mating end single contact grouping | |
| Insert Material: | |
| Plastic diallyl phthalate single mating end | |

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

26 single mating end single contact grouping

NSN 5935-00-945-7265

Electrical Receptacle Connector - Page 2 of 2



| Included Contact Type: |
|--|
| Round socket single mating end single contact grouping |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.