

View Online at <https://aerobasegroup.com/nsn/5935-00-945-9683>

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

2.067 inches

Overall Diameter:

1.625 inches

Environmental Protection:

Pressure proof and heat resistant and moisture resistant and oil tight and salt water resistant and vibration resistant

Cable Entrance Diameter:

Between 0.925 inches and 0.955 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

22-55 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet shell

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Rhodium single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber silicone class q single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Included Contact Quantity:

55 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces rhodium and contact surfaces silver

Precious Material And Weight:

0.055 rhodium grains, troy and 0.055 silver grains, troy

Precious Material:

Rhodium and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0