Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-946-1966

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.600 inches

Overall Height:

1.688 inches

Overall Width:

3.297 inches

Environmental Protection:

Shock resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.984 inches

Distance From Mounting Shoulder To Front Face:

0.656 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

66 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Jackscrew and shell

Shell Type:

Potting

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

NSN 5935-00-946-1966

Electrical Receptacle Connector - Page 2 of 2



Tor	minal Location:
	ck single mating end single contact grouping
	ntact Material:
	oper alloy single mating end single contact grouping
-	ntact Surface Treatment:
	Id single mating end single contact grouping and silver single mating end single contact grouping
	ert Material:
	stic diallyl phthalate single mating end
	minal Type:
	der well single mating end single contact grouping
	ell Material:
Ste	
	ell Surface Treatment:
	odize
	ert Material Specification:
	-m-19833, ty gdi-30 military specification single material response single mating end
	ell Guide Type And Location Designator:
As	
Inc	luded Contact Quantity:
	single mating end single contact grouping
	Iuded Contact Type:
Ro	und pin single mating end single contact grouping
Pre	ecious Material And Location:
Со	ntact surfaces gold and contact surfaces silver
Pre	ecious Material And Weight:
0.0	66 gold grains, troy and 0.066 silver grains, troy
Pre	ecious Material:
Go	ld and silver
Th	read Series Designator:
Un	c
She	elf Life:
N/a	I Contraction of the second
Uni	it Of Measure:
Dei	militarization:
No	
Fiig	g:
A03	39b0
Mil	-std (military Standard):
Mil	-m-19833 spec.