

View Online at <https://aerobasegroup.com/nsn/5935-00-946-4344>

Body Style:

Straight edge type w/mounting flange

Overall Length:

7.600 inches

Overall Height:

0.656 inches

Overall Width:

0.500 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

7.302 inches

Board Accommodated Length:

6.802 inches single board

Board Accommodated Width:

0.062 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1800.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Unable To Decode:

Unable to decode and unable to decode and unable to decode and unable to decode and unable to decode and unable to decode and
unable to decode and unable to decode and unable to decode and unable to decode

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

86 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.086 gold grains, troy and 0.086 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.