

View Online at https://aerobasegroup.com/nsn/5935-00-946-7679

Inread Utass: 2a Thread Direction: Right-hand Body Style: Straight shape, external coupling Overall Length: 1.940 inches Overall Length: 1.940 inches Overall Width: 0.812 inches Overall Width: 0.759 inches and 0.740 inches Distance From Mouting Shoulder To Front Face: Between 0.720 inches and 0.744 inches Distance From Mouting Shoulder To Front Face: Between 0.720 inches and 0.744 inches Distance From Mouting facility Mating End Quantity: 1 1 1 1 1 1 1 1 1 1 1 1 1	Thread Class:	
Tread Direction:         Right-hand         Body Style:         Straight shape, external coupling         Overall Length:         1.940 inches         Overall Height:         0.812 inches         Overall Height:         0.812 inches         Overall Width:         0.812 inches         Outhreaded Mounting Hole Diameter:         0.116 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 0.769 inches and 0.774 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.769 inches and 0.740 inches         Distance From Mounting facilities         Mating End Quantity:         Between 0.720 inches and 0.740 inches         Between 0.720 inches and 0.740 inches         Mating End Quantity:         1         Verated Device Type:         Back shell and coupling facility         Mating End Quantity:         147         String In Autoid:         Keyway or multiple keyway:         Insert Position In Deg:         String In Lengther:		
Right-hand         Body Style:         Straight shape, external coupling         Overall Length:         1.940 inches         Overall Height:         0.812 inches         Overall Height:         0.812 inches         Overall Height:         0.812 inches         Overall Height:         0.812 inches         Overall Midth:         0.812 inches         Outhreaded Mounting Hole Diameter:         0.116 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 0.769 inches and 0.774 inches         Distance Ectween Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.769 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         14.7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         Solid         Connector Locking Method:         Externally threaded shell		
Body Style:         Straight shape, external coupling         Overall Length:         1.940 inches         Overall Height:         0.812 inches         Overall Width:         0.812 inches         Overall Width:         0.812 inches         Overall Width:         0.812 inches         Outhreaded Mounting Hole Diameter:         0.116 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 0.769 inches and 0.774 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Mating End Quantity:         1         Contact Position Arangement Style:         1.4-7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         10.0         Shell Type:         Solid         Contact Locking Method:         Keymay or multiple keyway         Thread Style		
Straight sape, external coupling         Overall Length:         1.940 inches         Overall Height:         0.812 inches         Overall Width:         0.812 inches         Overall Width:         0.812 inches         Outhreaded Mounting Hole Diameter:         0.116 inches         Center Distance Between Mounting Facilities Parallel To Height:         Between 0.769 inches and 0.774 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         14-7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         0.00         Shell Type:         Solid         Contact Locking Method:         Reternally threaded shell         Thready Quy Per Inch (tpi):         20         Thread Size:         0.875 inches and 0.938 inches		
Overall Length:         1.940 inches         Overall Height:         0.812 inches         Overall Width:         0.812 inches         Overall Width:         0.812 inches         Unthreaded Mounting Hole Diameter:         0.116 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 0.769 inches and 0.774 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         1.4-7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         10.0         Shell Type:         Solid         Concetor Locking Method:         Externally threaded shell         Thready Gty Per Inch (tpi):         20         Thread Size:         0.875 inches and 0.938 inches         Insert Materia! <td></td> <td></td>		
1.940 inclust         Overall Height:         0.812 incluss         Overall Width:         0.812 incluss         Unthreaded Mounting Hole Diameter:         0.116 incluss         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 0.769 inches and 0.774 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.740 inches         Distance From Mounting facility         Mating End Quantity:         1         Contact Position Arrangement Style:         1.4-7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         10.0         Shell Type:         Solid         Contact Locking Method:         Externally threaded shell         Threaded Juper Inch (tpi):         20         Threaded Shell         Threaded Shell         Shell Shell Material:		
Overall Heigh:         0.812 inches         Overall Width:         0.812 inches         Unthreaded Mounting Hole Diameter:         0.116 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 0.769 inches and 0.774 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Mating End Quantity:         1         Context Position Arrangement Style:         14-7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         10.0         Shell Type:         Solid         Connector Locking Method:         Externally threaded shell         Thready dty Per Inch (tpi):         20         Thread Size:         0.875 inches and 0.938 inches         Insert Material:         Plastic diallyl phthalate single mating end	-	
0.812 inches         Overall Width:         0.812 inches         Unthreaded Mounting Hole Diameter:         0.116 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 0.769 inches and 0.774 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Mating End Quantity:         1         Context Position Arrangement Style:         14-7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         10.0         Shell Type:         Solid         Connector Locking Method:         Externally threaded shell         Thready Qip Per Inch (tpi):         20         Thread Size:         0.875 inches and 0.938 inches         Insert Material:		
Overall Width:         0.812 inches         Unthreaded Mounting Hole Diameter:         0.116 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 0.769 inches and 0.774 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         14-7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         10.0         Shell Type:         Solid         Connector Locking Method:         Externally threaded shell         Threaded Size:         0.875 inches and 0.938 inches         Insert Material:         Plastic diallyl phthalate single mating end         Between Colore of Size (Colore)         20         Thread Size:         0.875 inches and 0.938 inches         Insert Material:	-	
0.812 inches         Unthreaded Mounting Hole Diameter:         0.116 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 0.769 inches and 0.774 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         14-7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         10.0         Shell Type:         Solid         Connector Locking Method:         Raternally threaded shell<		
Unthreaded Mounting Hole Diameter:         0.116 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 0.769 inches and 0.774 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Maing End Quantity:         1         Contact Position Arrangement Style:         14-7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         10.0         Shell Type:         Solid         Connector Locking Method:         Externally threaded shell         Threaded Stell         Threaded shell         Threaded shell         Threaded Stell         0.875 inches and 0.938 inches         Insert Material:         Plastic diallyl phthalate single mating end		
0.116 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 0.769 inches and 0.774 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Mating End Quantity:         1         Context Position Arrangement Style:         14-7 single mating end         Polarization Method:         Keyway or multiple keyway         100         Shell Type:         Solid         Connector Locking Method:         Externally threaded shell         Thready Qty Per Inch (tpi):         20         Thread Size:         0.875 inches and 0.938 inches         Insert Material:		
Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.769 inches and 0.774 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.769 inches and 0.774 inches Distance From Mounting Shoulder To Front Face: Between 0.720 inches and 0.740 inches Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 14-7 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 10.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 20 Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end	Unthreaded Mounting Hole Diameter:	
Between 0.769 inches and 0.774 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         14-7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         10.0         Shell Type:         Solid         Connector Locking Method:         Externally threaded shell         Thready Qty Per Inch (tpi):         20         Thread Size:         0.375 inches and 0.938 inches         Insert Material:         Plastic diallyl phthalate single mating end		
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.769 inches and 0.774 inches Distance From Mounting Shoulder To Front Face: Between 0.720 inches and 0.740 inches Threaded Device Type: Back shell and coupling facility Mating End Quantity: Mating End Quantity: 1 Contact Position Arrangement Style: 14-7 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 10.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 20 Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	Center To Center Distance Between Mounting Facilities Parallel To Height:	
Between 0.769 inches and 0.774 inches         Distance From Mounting Shoulder To Front Face:         Between 0.720 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         14-7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         10.0         Shell Type:         Solid         Connector Locking Method:         Externally threaded shell         Thready Qty Per Inch (tpi):         20         Thread Size:         0.875 inches and 0.938 inches         Insert Material:         Plastic diallyl phthalate single mating end         Shell Material:	Between 0.769 inches and 0.774 inches	
Distance From Mounting Shoulder To Front Face: Between 0.720 inches and 0.740 inches Threaded Device Type: Back shell and coupling facility Mating End Quantity: Mating End Quantity: 1 Contact Position Arrangement Style: 14-7 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 10.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 20 Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
Between 0.720 inches and 0.740 inches         Threaded Device Type:         Back shell and coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         14-7 single mating end         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         10.0         Shell Type:         Solid         Connector Locking Method:         Externally threaded shell         Thready Qty Per Inch (tpi):         20         Thread Size:         0.875 inches and 0.938 inches         Insert Material:         Plastic diallyl phthalate single mating end         Shell Material:	Between 0.769 inches and 0.774 inches	
Threaded Device Type:Back shell and coupling facilityMating End Quantity:Mating End Quantity:1Contact Position Arrangement Style:14-7 single mating endPolarization Method:Keyway or multiple keywayInsert Position In Deg:10.0Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20Firead Size:0.875 inches and 0.938 inchesInsert Material:Plastic diallyl phthalate single mating endShell Material:	Distance From Mounting Shoulder To Front Face:	
Back shell and coupling facilityMating End Quantity:11Contact Position Arrangement Style:14-7 single mating endPolarization Method:Keyway or multiple keywayInsert Position In Deg:10.0Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20Firead Size:0.875 inches and 0.938 inchesInsert Material:Plastic diallyl phthalate single mating endShell Material:	Between 0.720 inches and 0.740 inches	
Mating End Quantity:1Contact Position Arrangement Style:14-7 single mating endPolarization Method:Keyway or multiple keywayInsert Position In Deg:10.0Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20Thread Size:0.875 inches and 0.938 inchesInsert Material:Plastic diallyl phthalate single mating endShell Material:	Threaded Device Type:	
1Contact Position Arrangement Style:14-7 single mating endPolarization Method:Keyway or multiple keywayInsert Position In Deg:10.0Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20Thread Size:0.875 inches and 0.938 inchesInsert Material:Plastic diallyl phthalate single mating endShell Material:	Back shell and coupling facility	
Contact Position Arrangement Style:14-7 single mating endPolarization Method:Keyway or multiple keywayInsert Position In Deg:10.0Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20Thread Size:0.875 inches and 0.938 inchesInsert Material:Plastic diallyl phthalate single mating endShell Material:	Mating End Quantity:	
14-7 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 10.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 20 Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	1	
Polarization Method:Keyway or multiple keywayInsert Position In Deg:10.0Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20Thread Size:0.875 inches and 0.938 inchesInsert Material:Plastic diallyl phthalate single mating endShell Material:	Contact Position Arrangement Style:	
Keyway or multiple keyway Insert Position In Deg: 10.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Chready Qty Per Inch (tpi): 20 Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	14-7 single mating end	
Insert Position In Deg: 10.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 20 Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	Polarization Method:	
10.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 20 Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	Keyway or multiple keyway	
Shell Type:   Solid   Connector Locking Method:   Externally threaded shell   Thready Qty Per Inch (tpi):   20   Thread Size:   0.875 inches and 0.938 inches   Insert Material:   Plastic diallyl phthalate single mating end   Shell Material:	Insert Position In Deg:	
Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 20 Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	10.0	
Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 20 Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	Shell Type:	
Externally threaded shell Thready Qty Per Inch (tpi): 20 Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	Solid	
Thready Qty Per Inch (tpi): 20 Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	Connector Locking Method:	
20 Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	Externally threaded shell	
Thread Size: 0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	Thready Qty Per Inch (tpi):	
0.875 inches and 0.938 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material:	20	
Insert Material: Plastic diallyl phthalate single mating end Shell Material:	Thread Size:	
Plastic diallyl phthalate single mating end Shell Material:	0.875 inches and 0.938 inches	
Shell Material:	Insert Material:	
	Plastic diallyl phthalate single mating end	
Aluminum alloy	Shell Material:	
	Aluminum alloy	



Shell Surface Treatment:

Cadmium

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0