

View Online at <https://aerobasegroup.com/nsn/5935-00-948-3838>

Body Style:

Straight shape, internal coupling

Overall Length:

0.750 inches

Overall Diameter:

0.390 inches

Environmental Protection:

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

Cable Entrance Diameter:

Between 0.115 inches and 0.135 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Compression nut

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification 1st treatment response single mating end single contact grouping and qq-s-365, type 2, grade a federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and silver

Shell Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification 1st treatment response and qq-s-365, type 2, grade a federal specification 2nd treatment response

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold and contact and body surfaces silver

Precious Material And Weight:

0.105 gold grains, troy and 0.105 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.