## NSN 5935-00-948-5867

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-948-5867
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
0.870 inches
Overall Height:
0.470 inches
Overall Width:
0.230 inches
Environmental Protection:
Vibration resistant
Distance Between Mounting Facility Centers:
0.625 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
7 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:

Terminal Type:

Solder well single mating end single contact grouping

Plastic diallyl phthalate single mating end

**Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end

## NSN 5935-00-948-5867

Electrical Receptacle Connector - Page 2 of 2



Inc	luded	Contact	Quantity:

7 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.007 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.