NSN 5935-00-949-2234

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-949-2234 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated from panel **Identification Code Color:** Clear **Body Style:** Threaded bushing mounted **Overall Length:** 1.000 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.625 inches **Overall Diameter:** 0.405 inches **Bushing Accommodation Hole Shape:** Round w/flat **Maximum Voltage Rating In Volts:** 750.0 ac **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger **Finger Accommodation Length:** 0.375 inches single finger **Bushing Thru-hole Accommodation Length:** 0.238 inches **Bushing Thru-hole Accommodation Width:** Between 0.250 inches and 0.255 inches **Current Rating In Amps:** 15.0 **Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches

Terminal Type:

Turret

NSN 5935-00-949-2234

Tip Jack - Page 2 of 2



Material:
Plastic, polyamide insulator
Material:
Plastic polyamide insulator
Precious Material And Location:
Spring contact surface gold
Precious Material:
Gold
Surface Treatment:
Nickel terminal
Surface Treatment:
Nickel terminal
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A03400