NSN 5935-00-949-3321

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-949-3321 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight edge type w/mounting flange **Overall Length: 3.187** inches **Overall Height:** 0.812 inches **Overall Width:** 0.328 inches **Unthreaded Mounting Hole Diameter:** 0.112 inches **Distance Between Mounting Facility Centers:** 2.937 inches **Board Accommodated Length:** 2.484 inches single board **Threaded Device Type:** Mounting bushing **Board Accommodated Width:** 0.062 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1800.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys **Shell Type:** Solid **Connector Locking Method:** Spring friction Thread Length: 0.219 inches

0.219 inches

Thread Size:

0.112 inches

NSN 5935-00-949-3321

Mil-std (military Standard):

Mil-m-19833 spec.

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Plastic diallyl phthalate
Shell Material Specification:
Mil-m-19833, type gdi-30 military specification single material response
Insert Material Specification:
Mil-m-19833, type gdi-30 military specification single material response single mating end
Included Contact Quantity:
30 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Bifurcated spring single mating end single contact grouping
Special Features:
Terminals 1 through 15 bent at 90 degree angle, polorization keys between contacts b-c/2-3 and e-f/5-6 and m-n/11-12 and r-p/13-14, colo
coded blue
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0