Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-949-3324

Thread Class: 2b **Thread Direction: Right-hand Body Style:** Straight edge type w/mounting flange **Overall Length:** 3.187 inches **Overall Height:** 0.812 inches **Overall Width:** 0.328 inches **Unthreaded Mounting Hole Diameter:** 0.112 inches **Distance Between Mounting Facility Centers:** 2.937 inches **Board Accommodated Length:** 2.484 inches all boards **Threaded Device Type:** Mounting bushing **Board Accommodated Width:** 0.062 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1800.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys Shell Type: Solid **Connector Locking Method:** Spring friction **Thread Length:** 0.219 inches **Thread Size:** 0.112 inches

Electrical Receptacle Connector - Page 2 of 2



Terminal Location	on:
Back single matir	ng end single contact grouping
Contact Material	l:
Copper alloy sing	le mating end single contact grouping
Contact Surface	Treatment:
Gold single matin	ig end single contact grouping
Insert Material:	
Plastic diallyl phth	nalate single mating end
Terminal Type:	
Tab, solder lug s	ingle mating end single contact grouping
Shell Material:	
Plastic diallyl phth	nalate
Shell Material Sp	pecification:
Mil-m-19833, type	e gdi-30 military specification single material response
Insert Material S	pecification:
Mil-m-19833, type	e gdi-30 military specification single material response single mating end
Included Contac	t Quantity:
30 single mating	end single contact grouping
Bushing Accom	modation Hole Shape:
Round	
Included Contac	st Type:
Bifurcated spring	single mating end single contact grouping
Special Features	S:
Terminals 1 throu	igh 15 bent at 90 degree angle, polarization keys between contacts c-d/3-4 and f-h/6-7 and p-r/13-14, color coded violet
Thread Series D	esignator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure	:
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military	Standard):
	C.