

View Online at <https://aerobasegroup.com/nsn/5935-00-950-2830>

Body Style:

Straight edge type w/mounting flange

Overall Length:

3.250 inches

Overall Height:

0.626 inches

Overall Width:

0.328 inches

Unthreaded Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Distance Between Mounting Facility Centers:

Between 2.932 inches and 2.942 inches

Board Accommodated Length:

2.479 inches single board and 2.489 inches single board

Board Accommodated Width:

Between 0.0548 inches and 0.0710 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Glass single mating end and plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping and mil-g-14548 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Included Contact Quantity:

15 single mating end single contact grouping

Included Contact Type:

Spring pincers single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.015 gold grains, troy and 0.015 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-14548 spec.