

View Online at <https://aerobasegroup.com/nsn/5935-00-951-5156>

**Thread Class:**

2a and 2a and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.821 inches

**Overall Diameter:**

0.500 inches

**Environmental Protection:**

Hermetic and weatherproof

**Distance From Mounting Shoulder To Front Face:**

0.400 inches

**Mounting Facility Thickness:**

0.093 inches

**Threaded Device Type:**

Back shell and coupling facility and mounting bushing

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Nonstd all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thready Qty Per Inch (tpi):**

32 and 32 and 32

**Thread Size:**

0.312 inches and 0.312 inches and 0.312 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold and silver all mating ends single contact grouping

**Insert Material:**

Glass all mating ends

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/double flat

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact and shell surfaces silver

**Precious Material And Weight:**

0.010 gold grains, troy and 0.110 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unef and unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0