## NSN 5935-00-951-7950

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-951-7950 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 7.990 inches **Overall Height:** 0.890 inches **Overall Width:** 1.271 inches **Distance Between Mounting Facility Centers:** 7.600 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: **Connector Locking Method:** 

Spring friction

**Thread Size:** 

0.138 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

## NSN 5935-00-951-7950

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416a federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-m-14 military specification single material response single mating end
Included Contact Quantity:
40 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Nuclear Hardness Critical Feature:
Hardened
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.040 gold grains, troy and 0.040 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.