Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-952-6192

Body Style:
Straight shape
Overall Length:
2.062 inches
Overall Height:
1.250 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Mounting Facility Centers:
1.750 inches
Cable Entrance Diameter:
0.421 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
18323 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
15.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
250.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
250.0 single mating end all contact groupings
Polarization Method:
Contact
Shell Type:
Solid
Connector Locking Method:
Shell twistlock
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Insert Material:
Plastic single mating end
Terminal Type:
Screw w/wire lock single mating end all contact groupings
Shell Material:
Copper alloy

NSN 5935-00-952-6192

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

Nickel

Included Contact Quantity:

2 single mating end 2nd contact grouping

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0