NSN 5935-00-954-1505

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-954-1505

Body Style: Straight shape **Overall Length:** Between 2.620 inches and 2.650 inches **Overall Height:** Between 0.419 inches and 0.439 inches **Overall Width:** Between 0.590 inches and 0.620 inches **Environmental Protection:** Moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.081 inches and 0.091 inches **Distance Between Mounting Facility Centers:** Between 2.401 inches and 2.411 inches **Mating End Quantity: Contact Position Arrangement Style:** 50 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Cadmium and chromate

Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response single mating end

NSN 5935-00-954-1505

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Quantity:
----------	---------	-----------

50 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.050 gold grains, troy and 0.050 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.