NSN 5935-00-954-1511

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-954-1511 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 1.680 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.160 inches **Overall Height:** 0.410 inches **Overall Width:** 0.500 inches **Environmental Protection:** Vibration resistant Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.343 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 34 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1950.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:**

Back single mating end single contact grouping

NSN 5935-00-954-1511

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Insert Material Specification:
Mil-m-19833, type gdi-30 military specification single material response single mating end
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
34 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Jackscrew type-female and location-right handandjackscrew type-male and location-left hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.034 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-19833 spec.