NSN 5935-00-954-2943

Cadmium and chromate

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-954-2943

Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
1.922 inches
Overall Diameter:
1.156 inches
Environmental Protection:
Moisture resistant
Cable Entrance Diameter:
0.375 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
14-91 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Connector Locking Method: Bayonet latch
Bayonet latch
Bayonet latch Connector Cable Strain Relief Method:
Bayonet latch Connector Cable Strain Relief Method: Cable clamp
Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location:
Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping
Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material:
Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping
Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material:
Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Rubber natural single mating end
Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Rubber natural single mating end Terminal Type:
Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Rubber natural single mating end Terminal Type: Crimp single mating end single contact grouping

NSN 5935-00-954-2943

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:

7 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.007 gold grains, troy and 0.007 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0