## NSN 5935-00-954-4479

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-954-4479



**Thread Class:** 2a and 2b **Body Style:** Straight shape **Overall Length:** 1.250 inches **Overall Height:** 0.270 inches **Overall Width:** 0.530 inches **Environmental Protection:** Shock resistant and vibration resistant and corrosion resistant **Distance Between Mounting Facility Centers:** 1.000 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 26 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Connector Locking Method:** Screw Thready Qty Per Inch (tpi): 56 Thread Size: 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate glass filled single mating end **Terminal Type:** Solder well single mating end single contact grouping

Included Contact Quantity:

26 single mating end single contact grouping

## NSN 5935-00-954-4479

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Arc resistant
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.026 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0