

View Online at https://aerobasegroup.com/nsn/5935-00-954-8993

## **Body Style:** Straight shape **Overall Length:** Between 1.542 inches and 1.572 inches **Overall Height:** 0.615 inches **Overall Width:** Between 0.355 inches and 0.375 inches **Unthreaded Mounting Hole Diameter:** 0.143 inches **Distance Between Mounting Facility Centers:** Between 1.245 inches and 1.255 inches Mating End Quantity: **Contact Position Arrangement Style:** 20 20-20 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Included Contact Quantity:** 20 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Test Data Document:**

1

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Electrical Receptacle Connector - Page 2 of 2



**Specification Data:** 

81349-mil-c-28748/6 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0