

View Online at <https://aerobasegroup.com/nsn/5935-00-954-9034>

Body Style:

Straight shape, flange mount, external coupling

Overall Length:

1.734 inches

Overall Height:

1.562 inches

Overall Width:

1.562 inches

Environmental Protection:

Vibration resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Distance From Mounting Shoulder To Front Face:

0.562 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

22-67 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

45.0

Shell Type:

Potting

Connector Locking Method:

Bayonet shell

Connector Cable Strain Relief Method:

Potting type

Terminal Location:

Back single mating end single contact grouping

Insert Material:

Plastic phenolic single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

25 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.