NSN 5935-00-955-1981

Straight shape, flange mount, external coupling

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-955-1981

Overall Length:
1.672 inches
Overall Height:
1.578 inches
Overall Width:
1.578 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.250 inches
Distance From Mounting Shoulder To Front Face:
0.587 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
22-55 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping

NSN 5935-00-955-1981

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
55 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.055 gold grains, troy and 0.055 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
18876-1063006455 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0