Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-955-4941

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape threaded
Overall Length:
1.105 inches
Overall Diameter:
Between 1.922 inches and 1.954 inches
Distance From Mounting Shoulder To Front Face:
Between 0.868 inches and 0.900 inches
Mounting Facility Thickness:
Between 0.062 inches and 0.250 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
22-32 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Size:
1.500 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings



Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

27 single mating end 2nd contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.041 gold grains, troy and 0.041 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0