NSN 5935-00-956-7330

Electrical Receptacle Connector - Page 1 of 2



6-7330

| View Online at https://aerobasegroup.com/nsn/5935-00-956 |
|--|
| Body Style: |
| Straight shape |
| Overall Length: |
| 2.590 inches |
| Overall Height: |
| 0.920 inches |
| Overall Width: |
| 0.500 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.150 inches |
| Distance Between Mounting Facility Centers: |
| Between 2.213 inches and 2.223 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 15 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Polarization Method: |
| Contact |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Included Contact Quantity: |
| 15 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| |

0.015 gold grains, troy

NSN 5935-00-956-7330

Electrical Receptacle Connector - Page 2 of 2



| Precious Material: |
|--------------------|
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

Fiig:

A039b0