## NSN 5935-00-957-1591

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-957-1591

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.714 inches and 2.744 inches

**Overall Height:** 

0.683 inches

**Overall Width:** 

Between 0.479 inches and 0.509 inches

**Environmental Protection:** 

Humidity resistant and corrosion resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.086 inches and 0.091 inches

**Distance Between Mounting Facility Centers:** 

Between 2.495 inches and 2.505 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

13w6 single mating end

**Contact Removability:** 

Nonremovable single mating end 2nd contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end 2nd contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Operating Tempurature Rating:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

**Features Provided:** 

Pre-tinned terminal

**Terminal Location:** 

Back single mating end 2nd contact grouping

**Contact Material:** 

Copper alloy single mating end 2nd contact grouping

**Contact Surface Treatment:** 

Gold single mating end 2nd contact grouping and copper single mating end 2nd contact grouping

**Insert Material:** 

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, tpe ii military specification 1st treatment response single mating end 2nd contact grouping or mil-g-45204, type i military specification 1st treatment response single mating end 2nd contact grouping and mil-c-14550, class 4 military specification 2nd treatment response single mating end 2nd contact grouping

## NSN 5935-00-957-1591

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end 2nd contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type ii, class 2 federal specification all treatment responses
Shell Material Specification:
Qq-s-698 federal specification single material response
Insert Material Specification:
Mil-p-19833, type gdi-30f military specification single material response single mating end or mil-m-14, type sdg-f military specification single
material response single mating end
Included Contact Quantity:
7 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end 2nd contact grouping
Special Features:
Reversed float mounts
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.007 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.