NSN 5935-00-957-2998

Plug-in Electronic Components Socket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-957-2998 **Body Material:** Plastic **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Top mount w/studs **Fabrication Method:** Molded **Overall Length:** 1.350 inches **Overall Height:** 0.620 inches **Overall Width:** Between 0.390 inches and 0.410 inches **Mounting Hole Diameter:** Between 0.075 inches and 0.080 inches **Distance Between Mounting Facility Centers:** Between 1.052 inches and 1.072 inches **Mounting Hole Style:** Two mounting holes/slots, in-line **Specific Equipment Accommodated:** Relay **Contact Maximum Current Rating In Amps:** 5.0 **Contact Material:** Copper alloy **Contact Surface Treatment:** Gold and silver **Accommodated Contact Quantity: Polarization Type:** Contact position **Projection Length Below Mounting Surface:** Between 0.115 inches and 0.135 inches **Mounting Method:** Threaded stud **Mounting Type For Which Designed:** Chassis

Thready Qty Per Inch (tpi):

NSN 5935-00-957-2998

Plug-in Electronic Components Socket - Page 2 of 2



Inread Size:
0.112 inches
Contact Position Arrangement Style:
Dual in line
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
$0.008 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.008 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A02300