# NSN 5935-00-957-4826

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-957-4826

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape	
Overall Length:	
1.630 inches	
Overall Height:	
0.850 inches	
Overall Width:	
0.560 inches	
Distance Between Mounting Facility Centers:	
1.312 inches	
Threaded Device Type:	
Mounting stud	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
26 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
7.5 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
500.0 single mating end single contact grouping	
Polarization Method:	
Guide pin/socket	
Thread Length:	
0.270 inches	
Thread Size:	
0.112 inches	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping and silver single mating end single contact grouping	
Insert Material:	
Plastic diallyl phthalate single mating end	
Terminal Type:	
Solder well single mating end single contact grouping	

## NSN 5935-00-957-4826

Electrical Receptacle Connector - Page 2 of 2



Mil-p-19833, ty gdi-30 military specification single material response single mating end

## **Included Contact Quantity:**

26 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

## **Precious Material And Weight:**

0.026 gold grains, troy and 0.026 silver grains, troy

#### **Precious Material:**

Gold and silver

#### **Test Data Document:**

81349-milc28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unc

#### **Specification Data:**

81349-mil-c-28748 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

\_

**Demilitarization:** 

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-p-19833 spec.