NSN 5935-00-957-8246

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-957-8246 **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 1.640 inches **Overall Height:** 1.188 inches **Overall Width:** 1.188 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** 0.532 inches **Mating End Quantity: Contact Position Arrangement Style:** 19p single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Spring friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:**

Gold single mating end single contact grouping

Insert Material:

Rubber single mating end

NSN 5935-00-957-8246

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
19 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.019 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0