NSN 5935-00-958-0003

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-958-0003
Thread Class:
2g
Thread Pitch Diameters:
+1.989/+2.000 inches
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
2.703 inches
Overall Height:
2.250 inches
Overall Width:
2.250 inches
Environmental Protection:
Moisture resistant and vibration resistant and shock resistant
Unthreaded Mounting Hole Diameter:
0.195 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.687 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.687 inches
Distance From Mounting Shoulder To Front Face:
1.000 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
16-322 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
135.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:

255.0

NSN 5935-00-958-0003

Electrical Receptacle Connector - Page 2 of 2



Chall Type:
Shell Type: Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
Thread Size:
2.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.020 gold grains, troy and 0.020 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Acme
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0