## NSN 5935-00-958-1893

Plug Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-958-1893

**Overall Length:** 1.457 inches **Overall Diameter:** 1.016 inches **Mating End Quantity: Contact Position Arrangement Style:** 8-dec single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Potting **Connector Locking Method:** Bayonet latch **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber synthetic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Insert Material Specification:** 

Mil-r-3065, ty s, grade sc717a, b, e military specification single material response single mating end

#### **Included Contact Quantity:**

8 single mating end single contact grouping

### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Special Features:**

Terminals e and f soldered together

# NSN 5935-00-958-1893

Plug Dummy Connector - Page 2 of 2



#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.008 gold grains, troy and 0.008 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.