

View Online at <https://aerobasegroup.com/nsn/5935-00-958-2063>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Electrical Insulation Feature:

Insulated completely

Identification Code Color:

Natural

Body Style:

Dual threaded bushing mounted

Overall Height:

1.000 inches

Mounting Bushing Length:

Any acceptable

Body Length:

Any acceptable

Body Width:

Any acceptable

Body Height:

Any acceptable

Bushing Accommodation Hole Shape:

Double round plain

Maximum Voltage Rating In Volts:

2000.0 ac

Accommodated Finger Type:

Test prod all fingers

Finger Accommodation Diameter:

0.080 inches all fingers

Finger Accommodation Length:

0.500 inches all fingers

Center To Center Distance Between Finger Accommodations:

0.750 inches

Bushing Thru-hole Accommodation Diameter:

0.250 inches

Center To Center Distance Between Bushing Thru-hole Accommodations:

0.750 inches

Capacitance In Picofarads:

2.0

Current Rating In Amps:

15.0

Mounting Facility Type And Quantity:

2 bushing

Thready Qty Per Inch (tpi):

32 and 32

Thread Size:

0.250 inches and 0.250 inches

Terminal Type:

Tab, solder lug

Material:

Plastic, styrene acrylonitrile insulator

Material:

Plastic styrene and plastic acrylonitrile insulator

Surface Treatment:

Nickel body

Surface Treatment:

Nickel body

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400