

View Online at https://aerobasegroup.com/nsn/5935-00-958-2502

| Thread Class: |
|--|
| 2a and 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Hood, top opening w/clamp |
| Overall Length: |
| 2.590 inches |
| Overall Height: |
| 1.870 inches |
| Overall Width: |
| 1.170 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 75 single mating end |
| Polarization Method: |
| Jackscrew |
| Shell Type: |
| Hood, top opening |
| Connector Locking Method: |
| Jackscrew |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Cable Opening Length: |
| 1.000 inches |
| Cable Opening Width: |
| 1.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.138 inches |
| Insert Material: |
| Plastic diallyl phthalate or plastic single mating end |
| Shell Material: |
| Aluminum |
| Shell Surface Treatment: |
| Anodize |
| Insert Material Specification: |
| Mil-p-19833 ty gdi-30 or ty gdi-30f military specification 1st material response or mil-m-14 military specification single material response |
| |

single mating end



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.