Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-958-4924

| Thread Class: |
|--|
| 2a and 2a |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.625 inches |
| Overall Diameter: |
| 0.875 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.863 inches |
| Threaded Device Type: |
| Coupling facility and mounting bushing |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| N single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thready Qty Per Inch (tpi): |
| 24 and 24 |
| Thread Size: |
| 0.625 inches and 0.625 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| |

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0