NSN 5935-00-958-9902

Electrical Receptacle Connector - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5935-00-956-9902
Body Style:
Right angle type
Overall Length:
3.344 inches
Overall Height:
0.469 inches
Overall Width:
0.719 inches
Environmental Protection:
Shock resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Mounting Facility Centers:
3.000 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
725.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-14548, type 2, cl 2 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping

Shell Material: Aluminum alloy

NSN 5935-00-958-9902

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Anodize
Insert Material Specification:
Mil-p-14, ty sdg-f military specification single material response single mating end
Included Contact Quantity:
23 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.023 gold grains, troy and 0.023 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-14548 spec.