Electrical Receptacle Connector - Page 1 of 2



0-959-4426

| View Online at https://aerobasegroup.com/nsn/5935-00-9 |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, latching |
| Overall Length: |
| 1.453 inches |
| Bushing Diameter: |
| 1.250 inches |
| Overall Width: |
| 1.438 inches |
| Diameter: |
| 1.438 inches |
| Threaded Device Type: |
| Mounting bushing |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 5 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 133.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Latch |
| Thread Length: |
| 0.563 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Thread Size: |
| 1.250 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| |

NSN 5935-00-959-4426

Electrical Receptacle Connector - Page 2 of 2



| Contact Material: |
|--|
| Copper alloy single mating end single contact grouping |
| Insert Material: |
| Rubber chloroprene class cr single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Zinc alloy |
| Included Contact Quantity: |
| 5 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round keyed |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |