NSN 5935-00-959-7726

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-959-7726 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Height:** 0.859 inches **Overall Width:** 0.438 inches **Distance Between Mounting Facility Centers:** 1.250 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 20 20-20 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Latch Thread Length: 0.266 inches **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic melamine single mating end **Included Contact Quantity:** 20 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-00-959-7726

Electrical Receptacle Connector - Page 2 of 2



Contact surfaces gold and contact surfaces silver Precious Material And Weight: 0.020 gold grains, troy and 0.020 silver grains, troy Precious Material:

Precious Material And Location:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0