## NSN 5935-00-959-7839

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-959-7839

**Thread Class:** 

2a and 2a and 2a

**Thread Direction:** 

Right-hand and right-hand and right-hand

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.833 inches

**Overall Diameter:** 

Between 1.734 inches and 1.766 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 1.078 inches and 1.098 inches

**Mounting Facility Thickness:** 

0.167 inches

**Threaded Device Type:** 

Back shell and coupling facility and mounting stud

**Mating End Quantity:** 

2

**Contact Position Arrangement Style:** 

24-28 single mating end

**Contact Removability:** 

Nonremovable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:** 

13.0 all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 all mating ends all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:** 

700.0 all mating ends all contact groupings

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

**Shell Type:** 

Solid

**Connector Locking Method:** 

Externally threaded shell

**Thread Length:** 

0.252 inches

Thready Qty Per Inch (tpi):

18 and 18 and 18

**Thread Size:** 

1.375 inches and 1.500 inches and 1.500 inches

## NSN 5935-00-959-7839

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back all mating ends all contact groupings
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Silver all mating ends all contact groupings
Insert Material:
Rubber all mating ends
Terminal Type:
Solder well all mating ends all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
24 all mating ends all contact groupings
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round socket all mating ends all contact groupings
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.048 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0