Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-959-8559

ľ	hread Class:
2	a and 2b
Т	hread Direction:
R	Right-hand and right-hand
B	Body Style:
Н	lood, side opening w/clamp
С	Overall Length:
1	.828 inches
С	Overall Height:
2	.406 inches
С	Overall Width:
0	.438 inches
С	Cable Entrance Diameter:
0	.594 inches
т	hreaded Device Type:
С	Coupling facility
N	lating End Quantity:
1	
С	Contact Position Arrangement Style:
1	4 single mating end
С	Contact Removability:
N	Ionremovable single mating end single contact grouping
С	Contact Maximum Current Rating In Amps:
1	3.0 single mating end single contact grouping
Ρ	Polarization Method:
J	ackscrew
S	Shell Type:
Н	lood, side opening
С	Connector Locking Method:
J	ackscrew-socket
С	connector Cable Strain Relief Method:
С	Cable clamp
Т	hread Size:
0	.138 inches and 0.138 inches
т	erminal Location:
В	ack single mating end single contact grouping
С	Contact Material:
С	Copper alloy single mating end single contact grouping
С	Contact Surface Treatment:
G	Sold single mating end single contact grouping

Plastic polytetrafluoroethylene single mating end

NSN 5935-00-959-8559

Electrical Plug Connector - Page 2 of 2



Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 14 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surface gold **Precious Material And Weight:** 0.014 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0